

1318+



Tally Dascom's 1318+ flat-bed serial dot matrix printer, is a 9 pin, 80 column printer with USB and parallel interfaces as standard. The 1318+ is ideal for front office applications in retail outlets, travel agents, train stations, banks and doctor's surgeries where space is limited.

With high quality output, an easy to use control panel and the option to use pre-cut or tractor fed paper, the 1318+ is ideal for counter-top printing applications such as, tickets, receipts, forms and multipart documents.

Highlights at a glance:

- Compact 9-pin flat-bed printer
- Up to 240 characters per second
- Ideal for front office applications
- Easy to use
- Long life ribbon
- Small footprint

The long life ribbon of the 1318+ means fewer ribbon changes, less downtime and lower running costs.

With print speeds of 240 characters per second (cps) and flexible media handling it keeps transactions smooth and the user happy.

The 1318+ is a reliable and easy to use printer, with low running costs and a space saving size.




Available Configuration:

- **1318+** Standard Product

1318+

Print Speed	240 cps (Fasted Draft); 180 cps (Draft), 45 cps (NLQ)
Print Method	Flat-Bed Serial Impact Dot Matrix
Resolution	Up to 144 x 240 dpi
Character Density	10, 12, 15, 17.1, 20 cpi, Proportional Spacing
Line Density	1, 2, 3, 4, 6, 8 lpi
Printhead life	400 Million Strokes per pin
Memory	64 kB
Standard Connectivity	USB 2.0 and parallel (Bi-directional)
Standard Emulation	Epson (ESC P), IBM 2380+
Fonts	HS Draft, Draft, Quadrato, Courier, OCR-A/B, 8 Barcodes
Consumables	Black Ribbon: 7 million characters
Standard Paper Handling	Friction and push tractor
Number of Copies	1 Original +4 (5-part forms)
Paper Type	Cut sheet and continuous forms
Paper Weight	52 - 100 gsm
Paper Size	2.16" to 11.7" wide (Cut Sheet); 4.0" to 10" wide (Fanfold)
Physical Weight	12.12 lbs
Physical Size	7.99" x 15.90" x 12.68" (H x W x D)
Power Voltage	120 V and 220 V models available
Power Consumption	<3.8 W (Stand-By), <28.8 W (Printing)
MTBF	10.000 hours
Drivers	Windows 2000, 2003 Server, XP, Vista, Windows 7
Temperature	0° C to +45° C
Humidity	10% to 80% (not condensing)
Acoustic	< 55 dB(A) (ISO 7779)
Warranty	1 year return to depot
Note	For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operation conditions.

DASCOM Americas Corporation
 421 West Main Street
 Waynesboro, Virginia
 USA 22980-3606
 Tel: 877 434 1377
 www.dascom.com

SERIAL MATRIX PRINTERS 
 MOBILE PRINTERS 
 FLATBED PRINTERS 
 THERMAL PRINTERS 