

7106



Tally Dascom's 7106 direct thermal printer offers reliability, precision and performance in desktop size, where space is limited.

The user friendly design of the printer allows a space saving vertical opening and an easy to use print mechanism ensures quick media loading. The clear panel enable simple and effective operation making it very simple to use.

The mechanism uses an all-metal construction ensuring reliable operation, a must for all industrial environments.

Highlights at a glance:

- Space-Saving Design Concept
- Easy and Quick media loading
- Serial and USB Standard
- Supports Zebra® and Datamax® emulation
- Optional Cutter and Peeler
- Internal 5 inch (125mm) media capacity

The 7106 offers a wide range of features and options usually only found on high performance machines. For example, it has an internal power supply providing the most reliable operation and avoiding problems usually associated with external power supplies.

The 7106 is easily integrated into existing systems, internal Ethernet interface is also available. In addition to this, the 7106 is also available with options such as a cutter and a peeler to meet industry requirements

Available Configurations:

- **7106** Standard Product

7106

Print Speed	6 ips
Print Width	4,1"/ 104,1 mm
Print Method	Direct Transfer
Print Length	0,25" - 32" (6,4 - 812 mm)
Resolution	203 dpi
Font Bitmapped	7 styles, TrueType
Printhead Life	Rated at 50 km
Memory	16 Mb SDRAM; 4 Mb Flash
Standard Connectivity	Serial (RS-232C), USB (Version 1.1)
Optional Connectivity	Parallel (IEEE 1284), Ethernet LAN (10/100 BaseT)
Standard Emulations	Auto-switching Zebra ZPL-II and Datamax I-Class, DMX400, Prodigy Plus
Consumables	Thermal direct paper and label
Media Width	0,77" - 4,65"/ 19,6 - 118 mm
Media Length	0,25" - 32" / 6,4 - 812,8 mm
Roll Diameter	Internally: 5" (125 mm), Externally: 8" with optional holder; Core size: 1" - 3" (25 to 76 mm)
Indexing	Full adjustable rear sensor and high resolution front sensor
Barcodes	Code11, Code39, Code93, Code128, I2of5, S2of5, EAN8, EAN13, ANSI, CODABAR, LOGMARS, MSI, Plessey, UPC A/E, POSTNET, Planet, Code49, PDF417, CODABLOCK, Maxi Code, DataMatrix, QR Code, RSS, TLC39
Physical Weight	7.9 lbs
Physical Size	9.1" x 11.27" x 7.2" mm (W x D x H)
Power Voltage	120 V and 220 V models available
Power Consumption	max. 12,9 W (Standby), 196 W (Operating)
Drivers	Windows XP/2003/Vista/7 (32/64 Bit)
Temperature	5° C - 35° C
Humidity	30% - 80% (not condensing)
Acoustic (ISO 7779)	< 55 dB(A)
Options	Auto cutter, Peeler, Parallel and LAN Interfaces
Warranty	One year return to depot on unit; 50 km or 6 months (whichever comes first) on printhead
Note	Accessories supplied: Head cleaning pen, Start-Up Guide, CD including: Manuals, Drivers and EasyConfig Tool

DASCOM Americas Corporation

421 West Main Street
Waynesboro, Virginia
USA 22980-3606
Tel: 877 434 1377
www.dascom.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 