

## LA48N, LA48W



*Tally*

The narrow-carriage LA48N and wide-carriage LA48W are designed for a broad spectrum of applications and are specially optimized for the DEC® environment. There's support for DEC®ANSI, IBM® ProPrinter® X24e, and Epson® ESC/P2 emulation.

The 24-pin print head produces clear, crisp output of texts and graphics. The printer has nineteen resident fonts and eight resident bar code fonts ensuring fast, high quality text and dependable bar code printing.

### Highlights at a glance:

- Print speeds up to 400cps @ 10cpi (LA48N); 448cps @ 10cpi (LA48W)
- 24-pin print head for clear, crisp output of text and graphics
- Standard Parallel and Serial interface
- Print head protection
- Auto interface switching on multiple I/F version
- Quiet operation

The printer offers simple switching of paper types and auto tear-off functionality. Parking continuous forms makes it easy to switch between continuous forms and single sheets. Continuous forms are automatically fed up to the tear-off position at the end of each job.

With a maximum noise level of only 49 dB(A) the LA48N and LA48W are very quiet printers compared with many competitive models.

#### Available Configuration:

- **LA48N** 80 Column Product
- **LA48W** 136 Columns Product

## LA48N, LA48W

<b>Print Speed</b>	480 cps (Fastest Draft); 360 cps (Draft), 113 cps (LQ) bei 10 cpi
<b>Resolution</b>	up to 360 x 360 dpi
<b>Throughput</b> (ECMA 132)	319 pages per hour
<b>Character Density</b>	10, 12, 15, 17.1, 18, 20 cpi
<b>Line Density</b>	1, 2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	400 million strokes per pin
<b>Memory</b>	128 kB
<b>Standard Connectivity</b>	Parallel (Bi-directional) and Serial RS 232
<b>Standard Emulations</b>	DEC ANSI PPL2, IBM ProPrinter, Epson LQ (ESC P/2)
<b>Fonts</b>	Courier, Prestige Elite, Boldface, Compressed, Draft, High-Speed Draft, Correspondence, Pica, Nimbus Sans <sup>®</sup> , Timeless, OCR-A/B, 8 Barcodes
<b>Consumables</b>	Ribbon: 4 million characters
<b>Standard Paper Handling</b>	Auto tear; manual continuous/cut sheet switch; manual paper thickness adjustment.
<b>Number of Copies</b>	1 Original + 5 copies
<b>Paper Type</b>	Continuous forms, multi-part forms
<b>Paper Weight</b>	60-120 g/m <sup>2</sup>
<b>Paper Format</b>	Width: 4" to 11.5"; Length: 3" to 14.3" (LA48N) Width: 4" to 16.5"; Length: 3" to 16.5" (LA48W)
<b>Physical Weight</b>	16 lbs (LA48N) 21 lbs (LA48W)
<b>Physical Size</b>	16.3" x 13" x 4.7" mm (B x T x H) (LA48N) 22.4" x 13" x 4.7" mm (B x T x H) (LA48W)
<b>Noise Level</b> (ISO 7779)	49 dB(A)
<b>Power Voltage</b>	120 V and 220 V models available
<b>Power Consumption</b>	10 W Stand-By
<b>Temperature</b>	+5° to +35° C; 20% to 80% humidity (not condensing)
<b>Print Volume</b>	8.000 pages per month
<b>MTBF</b>	20.000 hours
<b>Warranty</b>	1 year return to depot

### DASCOM Americas Corporation

421 West Main Street  
Waynesboro, Virginia  
USA 22980-3606  
Tel: 877 434 1377  
www.dascom.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 