

LA550N, LA550W



Tally

The dependable LA550N and LA550W offer class-leading performance. Flat push tractors drive forms through a straight paper path, resulting in delivery of invoices, shipping bills, labels, and statements time after time.

At up to 750 characters per second and with workloads to 26,000 pages per month, the LA550N and LA550W are ideal for tough, transaction printing. The LA550N and LA550W can be optionally configured with up to three input tractors.

Highlights at a glance:

- Print speeds up to 750 cps
- Full range of automatic features minimising operator intervention
- Ideal for ,On-Demand' and ,Batch' applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Serial interfaces standard
- Includes DEC PPL2 command set and MMJ Adapter

From the small 80-column footprint of the LA550N to the 136-column capacity of the LA550W, their rugged design and quiet operation equip them for the warehouse, the shipping dock or the front desk.

Back room durability combined with front-office 24-wire print quality and a variety of automated performance features make the LA550N and LA550W a serious solution for demand document pricing.




Available Configuration:

- **LA550N** 80 Column Product
- **LA550W** 136 Column Product

LA550N, LA550W

Print Sped	720 cps (Fastest Draft), 500 cps (Draft), 270 cps (DPQ), 180 cps (NLQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	446 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	400 million characters
Memory	128 kB
Standard Connectivity	Parallel (Bi-directional) and Serial RS232
Optional Connectivity	Ethernet 10/100BaseT
Standard Emulations	IDEC ANSI PPL2, IBM ProPrinter XL24, Epson LQ (ESC P/2)
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and Large Character Printing (LCP)
Consumables	Ribbon: 3.5 million characters (LA550N) or 5 million characters (LA550W)
Standard Paper Handling	Push tractors with paper parking and automatic gap adjustment (AGA).
Optional Paper Handling	Additional push tractor, front. Additional push tractor, rear. Front single bin automatic sheet feeder.
Number of Copies	Push tractor front: 1 Original + 5 copies; Push tractor rear: 1 Original +1 copy; Single sheet: 1 Original + 5 copies
Paper Type	Continous forms, single sheets
Paper Weight	60-120 g/m ²
Paper Format	Width: 3" to 10"; Length: 3" to 23" (LA550N) Width: 3" to 16.5"; Length: 3" to 23" (LA550W)
Physical Weight	22 lbs (LA550N) 35 lbs (LA550W)
Physical Size	18.1" x 11.8" x 11.6" (W x D x H) (LA550N) 23.6" x 11.8" x 11.6" (W x D x H) (LA550W)
Noise Level (ISO 7779)	53 dB(A)
Power Voltage	120 V or 230 V (selectable)
Power Consumption	40 Watt printing; <10 W Sleep Mode
Temperature	+10° to +35° C; 20% to 80% humidity (not condensing)
Print Volume	26.000 pages per month
MTBF	10.000 hours
Warranty	1 year return to base
Printer Drivers	Windows 2000/XP/Vista/7; Windows Server 2003/2008

DASCOM Americas Corporation
 421 West Main Street
 Waynesboro, Virginia
 USA 22980-3606
 Tel: 877 434 1377
 www.dascom.com

SERIAL MATRIX PRINTERS 
 MOBILE PRINTERS 
 FLATBED PRINTERS 
 THERMAL PRINTERS 