

T5040



Tally

With up to 600 characters per second (cps), the T5040 rapidly processes media of diverse types ranging from passbooks and cheques to A5 receipts and A4 information sheets.

The printer's flatbed design provides totally assured paper handling, and with advanced features such as Automatic Paper Alignment and Auto Gap Adjustment (AGA), they offer unsurpassed ease-of-use. Using Serial Impact technology - the most reliable and versatile method available of producing print - the T5040 is a durable, robust, dependable printer that supports a wide range of printing applications.

Highlights at a glance:

- Supports a wide variety of media
- Automatic gap adjustment of the print head
- Automatic alignment of forms and passbooks
- Automatic edge detection
- Ability to connect to multiple hosts simultaneously via parallel or USB, plus an optional second serial port
- Unrivalled transaction times - typical passbook 2.2 seconds
- DIN Letter 11.8 seconds

The standard T5040 supports cut forms via a serial interface connection and a secure command language, as demanded within the banking environment. As standard, USB and Parallel interfaces are included for flexibility of connection and single-station, multi-user operation. A second, plug in, serial interface is available as an upgrade option.

Also available are models with Magnetic Stripe encoding for reading accounts codes directly into the system minimizing user intervention.




Available Configuration:

- **T5040** Standard Product
- **T5040 MSR-H** with horizontal MSR

T5040

Print Speed	600 cps (Fasted Draft); 400 cps (Draft), 133 cps (NLQ)
Print Method	Flat-Bed Serial Impact Dot Matrix
Resolution	Up to 360 x 360 dpi
Character Density	10, 12, 15, 17.1, 20 cpi, Proportional Spacing
Line Density	1, 2, 3, 4, 6, 8 lpi
Printhead life	400 Million Strokes per pin
Memory	32 kB
Standard Connectivity	Parallel (Bi-directional), Serial (RS 232) and USB 2.0
Optional Connectivity	Model with second serial interface
Standard Emulation	IDM 4722, IBM ProPrinter XL24e, Epson (ESC P/2), Olivetti PR50/PR2/PR2e
Fonts	Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, OCR-A/B, 10 Barcodes
Consumables	Black Ribbon: 10 million characters
Standard Paper Handling	Friction and push tractor
Number of Copies	1 Original +4 (5-part forms)
Paper Type	Cut sheet and continuous forms with max. thickness of 2.0 mm
Paper Weight	60 - 260 gsm
Paper Size	2.8" to 9.4" wide
Physical Weigth	22 lbs
Physical Size	14.88" x 11" x 6.61" (W x D x H)
Power Voltage	120 V and 220 V models available
Power Consumption	<9 W (Stand-By), <73 W (Printing)
MTBF	10.000 hours
Drivers	Windows 2000, 2003 Server, XP, Vista, Windows 7
Temperature	10° C to +40° C
Humidity	15% to 75% (not condensing)
Acoustic	< 55 dB(A) (ISO 7779)
Warranty	1 year return to depot
Note	For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operation conditions.

DASCOM Americas Corporation
 421 West Main Street
 Waynesboro, Virginia
 USA 22980-3606
 Tel: 877 434 1377
 www.dascom.com

SERIAL MATRIX PRINTERS 
 MOBILE PRINTERS 
 FLATBED PRINTERS 
 THERMAL PRINTERS 