

Output Technology's PrintCenter™ 24 Series printers are a leader in the specialized, continuous-form laser market. With speeds of 24 pages per minute, they are the high speed, high quality laser printers you need for fast turnaround on continuous-form reports, checks and billing statements. Superior print accuracy and media handling make PrintCenter™ 24 Series printers ideal for batch printing tags, tickets, and labels.

**All Output Technology PrintCenter™ 24 printers offer a Limited One-Year On-Site Warranty.**



# PrintCenter™ 24

- HP LaserJet IV, PCL 5e, HP-GL/2, PCL/PJL Extensions and IGP 10/20/40 emulations
- 45 Scaleable Fonts, 8 Bitmap Fonts and 11 industry industry standard bar codes supported
- Profiler 24 software allows remote configuration of up to 10 application configurations paper profiles
- Optional Floor Stand / Power Stacker
- One year limited on-site service is standard and provides the utmost in convenience

# PrintCenter™ 24

## MODELS

PrintCenter 24 Model 1 & 2

## PRINT SPEED

24 pages per minute (1584 lpm @ 6 lpi)

## WORKLOAD

50,000 pages per month

## LIFETIME

Up to 3,000,000 pages

## RESOLUTION

300 x 300 dpi text and graphics

## COMPATIBILITY

### Emulations

Model 1: HP LaserJet IV® (PCL5e®)\*

Model 2: HP LaserJet IV® (PCL5e®)\*, IGP®

Auto switch between emulations (Model 2 only)

\*HP-GL/2, PCL / PJI Extensions

### Drivers

Windows 3.1, 95, 98, NT4.0, 2000, XP

## FONTS


45 Scalable fonts  
6 bitmap fonts with fix pitch  
16.67 cpi  
OCR-A and OCR-B  
2 Barcode Fonts Code 39

## BARCODES

Code 39  
2 of 5 industrial  
2 of 5 interleave  
EAN 8 and EAN 13  
Code 128  
UPC-A and UPC-E  
Codabar  
MSI  
Code 93  
Postnet  
KIX Code

## OPTIONS

Floor Standing Refolding Stacker



## ADVANCED FEATURES

### Pinpoint Registration

Adjust image registration to within 1/300th inch every 0.5 inch or every page.

### Remote Administration

Profiler 24: allows remote network administration of up to 10 application configurations.

### Variable Fuser Temperature

8 User controlled settings

### Reverse Landscape Function

Enables printing of wide carriage reports in compressed landscape format in sequential order from left to right.

## INTERFACES

IEEE 1284 Type B parallel

## PROCESSOR

AMD 29240 32 Bit RISC Processor

## CONSUMABLES

### Toner Kit:

Up to 16,000 pages @ 5% coverage

### OPC

Up to 30,000 pages

### Developer

Up to 100,000 pages

### Fuser Unit

Up to 300,000 pages

## PAPER HANDLING

### Type

Continuous 1-part, tractor fed

### Forms Size

3" to 33" (13mm to 838mm) L  
4" to 10" (101mm to 254mm) W

### Paper Advance

Adjustable 6-pin tractor

### Paper Path

Straight, front to back

### Media Specification

16-42 Lb. Paper  
Matrix On Labels  
8.25" (210mm) maximum print line width

## MEMORY

### Standard

8 MBytes Data Memory  
4 MBytes Flash Eprom Font Memory

### Expansion

Optionally expandable up to 32 mb

## PHYSICAL

### System

1 & 1/2 component toner, heat fused

### Photosensitive Material

Organic photoconductor (OPC)

### Weight

56.2lbs (25kgs)

### Physical Characteristics

18.11" (W) x 9.76" (H) x 19.61" (D)  
460mm (W) x 248mm (H) x 498mm (D)

### Acoustic Emissions

53 dBA  
47 dBA on standby

### Warm-up Time

< 3 minutes

### Time to 1st Print

< 20 seconds (Operating)  
< 30 seconds (Standby)

## POWER

100-120 VAC, 60 Hz or 220-240 VAC, 50 Hz

### Power Consumption

< 1000 watts maximum

## WARRANTY

1 year or 500,000 pages, whichever comes first (some restrictions apply)

## CERTIFICATIONS



## SERVICE

On-site service standard (U.S. only)

Specifications subject to change without notice.

Specifications subject to change without notice.



Corporate Office  
3808 N. Sullivan Rd. Bldg #3  
Spokane, WA 99216-1619  
509-536-0468  
800-393-7693 (USA Only)  
FAX: 509-533-1285

GSA Contract # GS-35F-0328J—Printers/Accessories  
GSA Contract # GS-14F-0669G—Ribbons

All company and product names are trademarks of their respective owners.

060-00165-01 Rev 5

[www.output.com](http://www.output.com)