

Output Technology's PrintCenter™ 45 printer has just widened your choices in continuous form non-impact printers. The PrintCenter™ 45 brings flexible printing solutions to many diverse business printing environments. This new printer provides impressive print speeds of 45 ppm (3,000 lpm) when printing full 11" x 16" continuous forms. The PrintCenter™ 45 utilizes flash fusing technology enabling printing on a wide variety of media including pressure sensitive labels. With its straight paper path, 500,000 pages per month duty cycle and integrated refolder, the PrintCenter™ 45 provides outstanding jam-free printing for your mid-range production printing requirements.



## **PrintCenter™ 45**

- Printing speeds up to 3000 lines per minute
- Forms overlay printing
- Automatic forms loading / 1st page printing
- Flat paper path for jam free operation
- Flash fusing for printing on heat sensitive media
- Integrated Gravity Stacker

# PrintCenter™ 45

## MODEL

PrintCenter45

## PRINT SPEED

3000LPM at 6LPI

(H) (W)

11" x 8.5" - 45ppm

11 x 14 <sup>7/8</sup> - 45ppm

8.5" x 11" - 58ppm

8.5" x 14" - 58ppm

## PRINTING METHOD

Electro photography process

LED array

## TONER

Single part dry toner

## TONER FUSING

Xenon flash fusing

## WORKLOAD

500,000 pages per month

## RESOLUTION

300 X 300 dpi

## PAPER HANDLING

Continuous 1-part tractor fed,

16 lb bond to 115 lb index

60 ~ 204 g/m<sup>2</sup>

## MAXIMUM PAPER SIZE

20" (H) x 16" (W)

## MAXIMUM PRINT AREA

20" (H) x 14.6" (W)

## COMPATABILITY

Emulations

HP PCL, Epson ESC/P, UL-PC Printer

Language, Windows

## Drivers

Windows 95, 98, NT, 2000 & XP.

## FONTS

PCL fonts compatible (70 AGFA Intelli-fonts)

## SPECIAL SYMBOLS

UL-PC Emulation

OCR-B Font

BAR Code: Code 25, Code 39, UPC/

EAN Code, Codabar

Dynamic Bar Code: Code 25, Code 39,

Code 128

PDF417

## CONTROLS

Graphic LCD pane

## POWER REQUIREMENTS

200-240vac/50-60Hz

Single Phase 3 Wire

## POWER CONSUMPTION

4500W (max) 300W (standby)

## OPERATING ENVIRONMENT

10 ~ 30 C / 30 ~ 80% RH

## ACOUSTIC

70 dBA printing 55 dBA idle

## SYSTEM ENVIRONMENT

DOS, UNIX, NOVEL, OS/2, MS Windows and others.

## INTERFACES

Parallel (IEEE-P 1284), TCP/IP

Print Controller

Optional

External Twinax / Coax

## PHYSICAL

Weight

Approximately 550 lbs (240 KG) including stacker

Dimensions

80.5 cm (W) x 125 cm (H) x

85 cm (D)

32" x 50" x 34"

## PRINTING FUNCTIONS

Rotate, enlarge draw line, draw circle, pan, reverse, background, wordgap, linegap, grid, frame, upperline, underline, portrait, landscape, cursor moving, form overlay, text and image overlay printing, CPI, LPI, and LPP selection windows printing.

## PAPERSTACKER

Integrated 3000 page capacity powered gravity stacker

Specifications subject to change without notice.



Corporate Office  
3808 N. Sullivan Rd. Bldg #3  
Spokane, WA 99216-1619  
509-536-0468  
800-468-8788 (USA Only)  
FAX: 509-533-1285

GSA Contract # GS-35F-0328J—Printers/Accessories  
GSA Contract # GS-14F-0669G—Ribbons

All company and product names are trademarks of their respective owners.

060-00299-01 Rev 2

[www.output.com](http://www.output.com)