

## 9022 Monochrome Laser Printer

The Small, Quick and Reliable 22 ppm Printer



### **Quick Printing.**

The 9022 monochrome laser printer represents the latest in affordable printing solutions for desktop and small workgroups. With excellent resolution and quick first page out times, the 9022 is the perfect choice for producing attractive documents quickly and precisely.

### **Robust Duty Cycle.**

With print speeds of up to 22 pages per minute and a peak duty cycle of 30,000 pages per month, the 9022 is an excellent choice for anyone in need of a fast and reliable monochrome laser printer. In addition to rapid operation, the lightweight and small footprint allow for versatile placement of the printer.

### **Multiple Connectivity Options.**

In order to meet the needs of virtually all IT administrators and business professionals, the 9022 can be configured for many different connectivity requirements including wireless 802.11b, 10/100 Ethernet, Parallel and High Speed USB 2.0.

- Print speed up to 22 pages per minute!
- Standard 16 MB memory
- Excellent cost of operation
- Workloads up to 30,000 pages per month
- Compact design allows for easy deployment
- Robust 166 MHz processor for rapid document creation
- Parallel and USB standard, 10/100 Ethernet optional
- Less than 10 seconds first page out time

---

#### Available Configuration:

9022i - 110v, Parallel/USB  
9022i - 110v, Parallel/USB, MICR-ready  
9022i - 110v, Parallel/USB, MICR, with drawer locks  
9022n - 110v, Parallel/USB/Ethernet  
9022n - 110v, Parallel/USB/Ethernet, MICR-ready  
9022n - 110v, Parallel/USB/Ethernet, MICR-ready, with drawer locks

# Features & Specifications

<b>Print Speed</b>	22 ppm
<b>Print Method</b>	Electro-photographic semiconductor laser
<b>Processor</b>	Samsung SPGPm 166 MHz
<b>Resolution</b>	1200 x 1200 dpi
<b>Time To 1st Page</b>	Less than 10 seconds
<b>Memory</b>	16 MB std / max 144 MB
<b>Standard Connectivity</b>	Parallel (Bi-directional IEEE 1284), Hi-Speed USB (v2.0). Automatic Interface Switching.
<b>Optional Connectivity</b>	Internal Ethernet (10Base-T & 100BaseT); Internal Wireless LAN (802.11b)
<b>Standard Emulation</b>	PCL 6 / PCL5e, Epson, IBM Proprinter
<b>Optional Emulation</b>	PostScript Level 3
<b>Fonts</b>	1 Bitit Map and 45 scaleable, 136 PS3 fonts (optional)
<b>Consumables</b>	5,000 pages toner; Initial toners supplied are up to 3,500 pages (based on @ 5% coverage letter page)
<b>STD Paper Handling</b>	Manual feed, 50-sheet multi-purpose tray (MPT) + 250-sheet universal cassette
<b>Opt'l Paper Handling</b>	2nd universal cassette accepts 250 sheets
<b>Duplexing</b>	Manual
<b>Paper Type</b>	Paper, transparencies, labels, heavy paper stock, envelopes
<b>Paper Weight</b>	16-43 lbs. (MPF*); 16-24 lbs. (Cassette)
<b>Paper Size</b>	Cassettes: Letter, A4, A5, Legal, Folio, Officio, Executive, ISO B5, JIS B5, 3"x5"; MPF: Accepts all cassette size plus A6 and Envelopes: Monarch, No.9, No.10, DL, C5
<b>Paper Output</b>	150-sheet face down
<b>Printable Area</b>	non-printable areas: Paper - 0.15" from each edge; Envelopes - 0.59" from left and 10mm from all other sides
<b>Physical Weight</b>	22.04 lbs. (incl. consumables)
<b>Physical Size</b>	10.94" x 14.1" x 17.8"
<b>Power Voltage</b>	120 V
<b>Power Frequency</b>	50/60 Hz
<b>Power Consumption</b>	Printing: 400W, Sleep Mode: 15W
<b>Compliance</b>	Energy Star compliant, Ozone-free
<b>Workload</b>	Up to 30,000 pages per month
<b>Drivers</b>	Windows 2003, XP, NT 4.0, Me, 95, 98 - GDI, PCL6, Linux compatibility, and optional Postscript 3
<b>Temperature</b>	50°F - 89.6°F
<b>Humidity</b>	10% - 80% relative humidity, non-condensing
<b>Acoustic</b>	Printing - 51 dB(A); Standby - 39 dB(A); Sleep Mode - background level
<b>Warranty</b>	One year, return to depot
<b>Option 1</b>	2nd cassette (250-sheet)
<b>Option 2</b>	128MB Memory
<b>Option 3</b>	SIMM with PostScript 3 & PCL Barcodes
<b>Options 4</b>	Internal Ethernet (10Base-T/100Base-T); Internal Wireless LAN (802.11b)
<b>Note</b>	Exceeding the monthly duty cycle will not void the warranty if TallyGenicom consumables and maintenance kits are used.



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Printed Date: 04/22/2007 Copyright © 2006 TallyGenicom, L.P.

4500 Daly Drive, Suite 100  
Chantilly, VA 20151  
T 800.436.4266  
www.tallygenicom.com

