

# Intelliprint 9035 Monochrome Laser Printer

Unmatched Fusion of Performance and Productivity.



### **Excellent Speed, Robust Duty Cycle.**

The 9035 prints at speeds up to 35 pages per minute with a first page out time of less than 9 seconds. In addition to the rapid printing speeds, the 9035 is capable of handling duty cycles of up to 150,000 pages per month. This kind of performance allows the 9035 to be relied upon in even the most demanding printing environments.

### **Productivity Enhancing Controller Architecture.**

The 9035 incorporates the Intelliprint controller architecture – a proprietary printing control technology developed by TallyGenicom to provide users with an unmatched fusion of performance and productivity enhancement. Features such as password-protected printing, saved job library and job accounting set the 9035 apart from the competition.

### **Intelliprint controller architecture**

In addition to the productivity enhancements offered by the Intelliprint controller architecture, the 9035 also boasts a class-leading 405 MHz processor, Adobe PostScript 3 and PCL6 and PCL5e functionality.

- Less than 9 seconds first page output time
- 1200 x 1200 dpi at up to 35 ppm
- Powerful 405 MHz RISC processor processor
- Intellifilter for compatibility with legacy print data streams
- Intelliprint controller
- Adobe PostScript 3, PCL6, PCL5e
- Optional duplex printing
- Duty cycle of 150,000 images per month
- One year on-site warranty

---

#### Available Configuration:

- 9035N** - Ethernet, Parallel, USB, PS3
- 9035ND** - Ethernet, Parallel, USB, PS3, with duplexer
- 9035NDT** - Ethernet, Parallel, USB, PS3, with duplexer and extra tray
- 9035M** - MICR, Ethernet, Parallel, USB, PS3
- 9035ME** - MICR-extended security laser printer, e-net, PS3

# Intelliprint 9035 Monochrome Laser Printer

## Features & Specifications

<b>Print Speed</b>	35 ppm
<b>Print Method</b>	Electro-photographic semiconductor laser with Intelliprint Controller
<b>Processor</b>	MIPS R5000 405 MHz
<b>Resolution</b>	1200 x 1200 dpi
<b>Time To 1st Page</b>	Less than 9 Seconds
<b>Memory</b>	64MB expandable to 320MB (2 slots); Optional 20GB (or higher) hard disk
<b>Standard Connectivity</b>	10/100Base-T Ethernet; TCP/IP, EtherTalk, Bonjour; IEEE 1284 parallel; Hi-Speed USB 2.0 480 Mb/s auto interface switching
<b>Standard Emulation</b>	PostScript 3; PCL6 with PjL, PCL5e
<b>Print Monitor</b>	SNMP, Printer MIB, e-mail status, and Web-based status and control, TGenAdmin
<b>Fonts</b>	136 Adobe PostScript fonts; 86 Type 1 PCL
<b>Consumables</b>	Single element toner cartridge with 17,000 pages (at 5%). New printer comes with 10,000 letter/A4 yield capacity.
<b>STD Paper Handling</b>	550-sheet tray; 150-sheet tray
<b>Opt'l Paper Handling</b>	550-sheet feeder tray (up to 2 additional)
<b>Duplexing</b>	Optional
<b>Paper Type</b>	Sheet paper, transparencies, bond, labels, envelopes, and thick media
<b>Paper Weight</b>	16 to 58 lbs (60 to 216 g/m <sup>2</sup> ) in simplex and duplex modes
<b>Paper Size</b>	Letter, executive, legal, folio, A4, A5, A6, B5, statement; Envelopes: Com10, Monarch, DL, C5; Custom sizes: 3.88 to 8.50 W by 5.83 to 14.00 L (tray 1 and 2 only); Officio (8.5" x 13.38" - supported as a custom size in tray #1 or #2)
<b>Paper Output</b>	500-sheet face-down top output; Optional cassette: 500-sheet offset catch tray
<b>Physical Weight</b>	45 lbs. (20.6 kg)
<b>Physical Size</b>	15.9" x 16.6" x 18.3" (404x 422 x 465 mm)
<b>Power Voltage</b>	100/120-127 VAC, 50/60 Hz; Current: 7 amps
<b>Compliance</b>	Energy Star compliant, Ozone-free; UL950, FCC part 15 Class B, ICES 003, CISPR22 Class B, FDA CDRH, cUL, CE, GS, IEC 825, GOST (Russia), SABS (S. Africa), and C-Tick (Australia)
<b>Workload</b>	Up to 150,000 pages per month
<b>Forms Software</b>	Intellifilter; Optional: Intellipress
<b>Drivers</b>	XP, 2003, 95, 98, 2000, Me, NT 4.0; Adobe PostScript and PCL drivers included; Unix and Linux compatibility
<b>Temperature</b>	Operating: 41° F - 95° F (5° to 35° C)
<b>Humidity</b>	Operating: 15%-85% Non-Condensing
<b>Acoustic</b>	Printing - 49.5 dB(A); Standby - 35 dB(A)
<b>Warranty</b>	One year on-site
<b>Option 1</b>	Add-on tray - 550 sheet feeder; duplexer; offset catch tray
<b>Option 2</b>	128MB DIMM; 256MB DIMM
<b>Option 3</b>	Intelliprint Barcode Module; Intelliprint Barcode/Real Time Clock Module; Intelliprint Real Time Clock
<b>Options 4</b>	Hard disk
<b>Option 5</b>	RS232 interface
<b>Note</b>	Exceeding the monthly duty cycle will not void the warranty if TallyGenicom consumables and maintenance kits are used. Toner saver mode provides up to 40% savings.



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Printed Date: 04/22/2007 Copyright © 2006 TallyGenicom, L.P.

4500 Daly Drive, Suite 100  
Chantilly, VA 20151  
T 800.436.4266  
www.tallygenicom.com

