

The PrintStationS100 from Output Technology is one of the new generation of high performance serial impact printers designed for the heavy-duty printing needs in administrative, industrial and logistics environments. With a speeds of up to 1100 cps, the PrintStationS100 printer is the ideal solution for applications demanding superior reliability. The printer automatically senses form thickness and adjusts the print head gap. With convenient zero-tear capability, the PrintStationS100 printer is truly a demand document performer. An optional second set of tractors permits automatic switching between multiple paper paths.



PrintStationS100 TM

- Speeds up to 1100 cps provide quality printing in less time
- Auto forms thickness sensing and adjustment
- Optional second tractor for co-resident continuous forms
- Straight paper path for reliable jam-free printing
- Windows Plug and Play compatibility allows for effortless installation

PrintStationS100™

MODELS

PrintStationS 100

PRINTING TECHNOLOGY

18 Pin Serial Matrix

WORKLOAD

PrintStationS 100: 65,000 pg/
mo

RELIABILITY - MTBF

10,000 hours

COMPATIBILITY

Emulations

IBM Proprinter III XL,
2381 Personal Printer,
Epson FX Series, ANSI,
CPG Native Commands

CONTROL PANEL

External Control Keys
On-line/off-line, shift, program/
pitch, load/form feed, macro/
path, font/park
External Indicator Lights
Ready, program, shift
LCD Display

GRAPHICS

Technique
Dot addressable
Resolution
Horiz. 60, 72, 80, 90, 120,
180, 240
Vert. 72, 144

MISCELLANEOUS

Acoustic
<54 dBA
Printhead Life
800 million characters

PrintSpeed

<u>Burst Speed</u>	<u>PrintStationS 100</u>
HSDraft (10cpi)	1100 cps
Draft (10cpi)	800 cps
Draft (12cpi)	960 cps
Draft (15cpi)	960 cps
LQ (10cpi)	240 cps
LQ (12cpi)	240 cps
LQ (15cpi)	240 cps

WARRANTY 1 Year depot or factory (U.S. only)

SERVICE Factory Express Service available (U.S. only)

Ribbon
Clean hands cartridge
>25 million character life

Drivers

Windows 3.1, 95, 98, 2000,
NT4.0, XP, VISTA

CHARACTER SETS

PC standard sets CS 1 & CS 2
IBM Code Pages
ISO Char sets, Epson, ANSI

BARCODES

UPC-A, UPC-E, EAN-8, EAN-
13, UPC/EAN ADD-ON 2,
UPC/EANADD-ON 5, Code 2
of 5 Bidirectional / Interleaved /
Industrial / Matrix, Code 39,
Code 128, Code 11, Code 93,
MSI, Codabar, POSTNET

RESIDENT FONTS

Draft, Courier, Gothic, Pres-
tige, Script, Presentor, OCR-A,

PAPER HANDLING

Type
Up to 8-part (original +7)
Tractor fed, 0.025" (0.56mm)
maximum thickness
Line Length
Up to 13.6" (345mm)
Paper Width
Up to 17" (406mm)
Paper Advance
Standard-
Lower push tractor feed
Zero tear-off
Paper parking
Auto forms thickness and ad-
justment
Optional-
Second lower push tractor feed
for co-resident continuous
forms
Forms Length
3.0" (76.2mm) to
17.5" (444.5mm) in
0.5" (13mm) increments, 4
metric sizes
Slew Rate
15" (381mm) per second
Copies
1 + 7

PHYSICAL

26.37" wide (670mm)
17.72" deep (450mm)
12.59" high (320mm)
46.29 lbs. (21kg)

POWER

120 VAC 60 Hz
220 VAC 50 Hz
Power Consumption
120 watts max, 30 watts
standby

Specifications subject to change without notice.



Corporate Office
3808 N. Sullivan Rd. Bldg #3
Spokane, WA 99216-1619
509-536-0468
800-393-7693 (USA Only)
FAX: 509-533-1285

GSA Contract # GS-35F-0328J—Printers/Accessories
GSA Contract # GS-14F-0669G—Ribbons

All company and product names are trademarks of their
respective owners.

060-00299-01 Rev 2

www.output.com