

The PrintStationS Series from Output Technology is a new generation of high performance serial impact printers designed for the heavy-duty printing needs in administrative, industrial and logistics environments. With speeds ranging from 600 cps to 1050 cps, the PrintStation Series printers are the ideal solution for applications demanding superior reliability. The printers automatically sense form thickness and adjust the print head gap. With convenient zero-tear capability, PrintStationS Series printers are truly demand document performers. An optional second set of tractors permits automatic switching between multiple paper paths.



PrintStationS 60/70™

- Speeds from 600 cps up to 1055 cps provide quality printing in less time
- Auto forms thickness sensing and adjustment
- Optional second tractor for co-resident continuous forms
- Straight paper path for reliable jam-free printing
- Windows Plug and Play compatibility allows for effortless installation

PrintStations 60/70™

MODELS

PrintStationS 60
PrintStationS 70

PRINTING TECHNOLOGY

24 Pin Serial Matrix

WORKLOAD

PrintStationS 60: 45,000 pg/mth
PrintStation 70: 50,000 pg/mth

RELIABILITY - MTBF

10,000 hours

COMPATIBILITY

Emulations
IBM Proprinter III, IBM Personal Printer 2381, Epson FX Series
Drivers
Windows 3.1, 95, 98, 2000, NT4.0, XP, VISTA

CONTROL PANEL

External Control Keys
On-line/off-line, shift, program/pitch, load/form feed, macro/path, font/park
External Indicator Lights
Ready, program, shift
LCD Display

GRAPHICS

Technique
Dot addressable
Emulations
IBM Proprinter XL24/XL24 AGM, 2391+ Personal Printer,
Epson ESC/P LQ series, Geni-com ANSI, CPG Native Commands
Resolution
Horiz. 60, 80, 90, 120, 180, 240, 360
Vert. 60, 72, 180, 360

PAPER HANDLING

Type
Up to 8-part (original +7)
Tractor fed, 0.025" (0.56mm) maximum thickness
Line Length
Up to 13.6" (345mm)
Paper Width
Up to 17" (406mm)
Paper Advance
Standard-
Lower push tractor feed
Zero tear-off
Paper parking
Auto forms thickness and adjustment
Optional-
Second lower push tractor feed for co-resident continuous forms
Forms Length
3.0" (76.2mm) to 17.5" (444.5mm) in 0.5" (13mm) increments, 4 metric sizes
Slew Rate
15" (381mm) per second

PrintSpeed

Burst Speed	PrintStationS 60	PrintStationS 70
Draft (10cpi)	600 cps	700 cps
Draft (12cpi)	720 cps	840 cps
Draft (15cpi)	900 cps	1050 cps
Best Draft (10cpi)	350 cps	380 cps
Best Draft (12cpi)	420 cps	460 cps
Best Draft (15cpi)	525 cps	580 cps
NLQ (10cpi)	232 cps	260 cps
LQ (10cpi)	116 cps	133 cps

PHYSICAL

26.37" wide (670mm)
17.72" deep (450mm)
12.59" high (320mm)
46.29 lbs. (21kg)

POWER

120 VAC 60 Hz
220 VAC 50 Hz
Power Consumption
116 watts max, 22 watts standby
ENERGY STAR® Compliant

WARRANTY 1 Year depot or factory (U.S. only)

SERVICE Factory Express Service available (U.S. only)

CHARACTER SETS

PC standard sets CS 1 & CS 2
IBM Code Pages
ISO Char sets, Epson, ANSI

BARCODES

UPC-A, UPC-E, EAN-8, EAN-13, UPC/EAN ADD-ON 2, UPC/EANADD-ON 5, Code 2 of 5 Bidirectional / Interleaved / Industrial / Matrix, Code 39, Code 128, Code 11, Code 93, MSI, Codabar, POSTNET

RESIDENT FONTS

Draft, Courier, Gothic, Prestige, Script, Presentor, OCR-A, OCR-B

MISCELLANEOUS

Acoustic
<54 dBA
Printhead Life
700 million characters
Ribbon
Clean hands cartridge
>15 million character life

INTERFACES

Type (Std)
Centronics Bi-directional Parallel
RS-232/C and RS-422/A Serial
Baud Rates 300 to 38400 bps

Type (optionl)
Internal Ethernet 10/100 baseT
External Twinax/Coax Inter-

Specifications subject to change without notice.



Corporate Office
3808 N. Sullivan Rd. Bldg #3
Spokane, WA 99216-1619
509-536-0468
800-393-7693 (USA Only)
FAX: 509-533-1285

GSA Contract # GS-35F-0328J—Printers/Accessories
GSA Contract # GS-14F-0669G—Ribbons

All company and product names are trademarks of their respective owners.

060-00299-01 Rev 2

www.output.com