

Powerful, Entry-Level Line Printer

T6065



The T6065 delivers flawless operation under adverse conditions. Inventors of line matrix printing, Tally has equipped this printer with distinct advantages in print quality, speed and functionality.

Superior print quality is achieved by a special impact element that creates a uniform, solid dot image. Font styles, character sizes and print attributes can be mixed on a single line, and Tally's exclusive Read/Right bar code algorithm creates sharp bar codes with no loss of throughput.

For maximum speed and throughput, a controller featuring "Page Segment Architecture" intelligently arranges data into segments prior to printing. Text and graphics print in just one pass with no forms reversal.

The T6065 is designed to produce time sensitive, large volume critical business documents at very low cost. Critical applications such as high quality multi-part printing on invoices, reports, special labels, or bar coded media are ideal tasks for this product.

With the exceptional price/performance and 52 dB(A) quiet operation, the T6065 is ready to meet the toughest challenges for business today, tomorrow and well into the next century.

- **Best price/performance in mid range; unlimited duty cycle**
- **PC/LAN compatible**
- **Quick-change, clean-hands ribbon cartridges**
- **Flash memory for easy program updates**
- **Straight paper path for excellent forms handling, up to 6-part forms**
- **Excellent connectivity options including Twinax/Coax, Ethernet, IPDS & IPDS over TCP/IP**
- **Stored-energy hammer bank technology for highest reliability**
- **Wide range of emulations and user-installable I/O modules with "hot" interfaces**
- **QMS® Code V™ and Printronix® Graphics Language (PGL) compatibility for industrial graphics and bar codes**

Tally®
Computer Printers

FEDERAL, STATE & LOCAL GOVERNMENT	MANUFACTURING, TRANSPORTATION/DISTRIBUTION	DIRECT MAIL/SERVICE BUREAUS
<ul style="list-style-type: none"> • ISO 9001 certified • Print tax forms, payroll checks, inventory reports and invoices • Energy Star compliant 	<ul style="list-style-type: none"> • Print pick lists, shipping labels and freight bills • Excellent readability on all industry-standard bar codes • Jam-free operation • Operates in harsh environments • Handles inventory labels and heavy stock 	<ul style="list-style-type: none"> • USPS POSTNET bar code certified • Ideal for long, unattended print runs • Rugged design, high speed, high workload

Powerful, Entry-Level Line Printer

Features & Specifications	T6065
Print Technology	Line impact dot matrix
Print Speed	Text: 650 lines per minute, draft: 488 lines per minute, data processing: graphics: 73 inches per minute
Workload	118,000 pages per month
Acoustic Level	52 dB(A); Enclosed Pedestal
Character Printing Modes	Constant density fonts; enhanced fonts
Character Sets	52 language sets
Characters Per Inch	5, 6, 6.7, 7.5, 8.3, 8.6, 10, 12, 13.3, 15, 16.7, 17.1, 20 cpi
Lines Per Inch	1.5, 2, 3, 4, 5, 6, 8, 9, 10 & 12 (plus variable line spacing)
Fonts	Draft, Data processing, Courier, Gothic, OCR A & B
Character Styles	Bold, italic, superscript, subscript, underline, overline, and strikethrough
Graphics Resolution	Maximum: 240 x 288 (H x V)
Graphics Compatibility	Tally Industrial Graphics; QMS® CODE V™ Version 2; Printronix® PGL
Bar Codes	Code 39, Code 128, Interleaved 2 of 5, UPC-A, UPC-E, EAN 8, EAN 13, EAN 128, Codabar, Identicon 2 of 5, MSI, POSTNET
Control Panel	Alphanumeric display (six languages) provides complete access to printer operation, configuration, calibration and test features. Includes lockout feature.
Paper Handling	Straight paper path, four tractor system, quick access feature - easy access to forms and labels, paper out and paper motion detection, forms position retained in non-volatile memory.
Print Media	Up to 6-part forms, forms thickness maximum .025", weight: 15-100 lb. stock
Paper Sizes	Width: 2.5" - 17.25", forms length: 1 - 255 lines
Paper Advance	Slew Speed: 16 inches per second (max.)
Standard Interface	Serial RS-232 (up to 38.4K Baud) and IEEE-1284 Compliant Centronics Parallel (both parts hot, and active port selected automatically)
Standard Emulations	Tally Line Printer, Printronix® P600 and P6000, HP 2564C, DEC® LG01, Epson® FX100, Genicom® ANSI & IBM® Proprinter III XL
Ribbon	Easy-load, clean-hands cartridges, 25, 50 & 150 million characters
Physical (H x W x D)	Tabletop: 15.8" x 31.5" x 23.2", 90 lbs.; Tabletop on Stand: 41.4" x 31.5" x 23.7", 120 lbs. Enclosed Cabinet: 40.6" x 31.5" x 23.2", 142 lbs.
Power Requirements	90 - 130/180 - 264 V, 57 - 63/47 - 53 Hz (auto-ranging)
Environmental	Temperature range: 10°C to 40°C (operating); -20°C to 60°C (non-operating) Humidity: 10% to 90% non-condensing (operating); 5% to 95% non-condensing (non-operating)
Optional Interfaces	FourPlex I/O: Twinax, Coax, Serial and Parallel, IPDS for FourPlex LANPlex I/O: Ethernet (10BaseT/100BaseT), Serial and Parallel, IPDS for LANPlex Extended Parallel I/O: Dataproducts Standard, Dataproducts Long Lines; Serial and Parallel. FourPlex and LANPlex also available as factory configured models



BSI ISO 9001: 1994
Certificate No. FM 28149



6/00. Specifications subject to change without further notice. All product and brand names are trademarks of the respective companies.

Tally Printer Corp.

8301 South 180th Street, P.O. Box 97018, Kent, WA 98064-9718
Telephone (425) 251-5524, 1-800-843-1347, Fax: (425) 251-5520

<http://www.tally.com>

Tally[®]
Computer Printers



T6065 Enclosed Pedestal



T6065 Print Stand